



FlashPure Cartridges

Technical data sheet



		BUCHI part number	Column volume	Max. pressure	Default flow rate	Loading capacity	Particle shape	Particle size	Pore size	Surface area	Carbon content	End capping
FlashPure EcoFlex												
FlashPure EcoFlex Silica	4g, 20pcs	140000021	6mL	300psi / 20bar	15mL/min	4mg-0.4g 0.1-10%	Irregular	40-63µm	55-75Å	470-530m ² /g	N/A	No
	12g, 18pcs	140000022	20mL	300psi / 20bar	30mL/min	12mg-1.2g 0.1-10%	Irregular	40-63µm	55-75Å	470-530m ² /g	N/A	No
	25g, 12pcs	140000023	3mL	300psi / 20bar	32mL/min	25mg-2.5g 0.1-10%	Irregular	40-63µm	55-75Å	470-530m ² /g	N/A	No
	40g, 12pcs	140000024	50mL	300psi / 20bar	40mL/min	40mg-4.0g 0.1-10%	Irregular	40-63µm	55-75Å	470-530m ² /g	N/A	No
	80g, 10pcs	140000025	110mL	250psi/ 17bar	60mL/min	80mg-8.0g 0.1-10%	Irregular	40-63µm	55-75Å	470-530m ² /g	N/A	No
	120g, 10pcs	140000026	155mL	250psi/ 17bar	85mL/min	120mg-12g 0.1-10%	Irregular	40-63µm	55-75Å	470-530m ² /g	N/A	No
	220g, 6pcs	140000027	280mL	180psi/ 12bar	120mL/min	220mg-22g 0.1-10%	Irregular	40-63µm	55-75Å	470-530m ² /g	N/A	No
	330g, 5pcs	140000028	430mL	180psi/ 12bar	130mL/min	330mg-33g 0.1-10%	Irregular	40-63µm	55-75Å	470-530m ² /g	N/A	No
	800g, 3pcs	140000029	1050mL	100psi / 7bar	180mL/min	800mg-80g 0.1-10%	Irregular	40-63µm	55-75Å	470-530m ² /g	N/A	No
	1600g, 2pcs	140000030	2000mL	100psi / 7bar	200mL/min	1.6g-160g 0.1-10%	Irregular	40-63µm	55-75Å	470-530m ² /g	N/A	No
	3000g, 1pcs	140000031	3910mL	100psi / 7bar	200mL/min	3.0g-300g 0.1-10%	Irregular	40-63µm	55-75Å	470-530m ² /g	N/A	No

		BUCHI part number	Column volume	Max. pressure	Default flow rate	Loading capacity	Particle shape	Particle size	Pore size	Surface area	Carbon content	End capping
FlashPure EcoFlex Alumina Neutral	8g, 20pcs	140000095	6mL	300psi / 20bar	15mL/min	8mg-0.32g 0.1-4%	Irregular	50-75µm	50-70Å	140-170m ² /g	N/A	No
	24g, 18pcs	140000096	20mL	300psi / 20bar	30mL/min	24mg-1.0g 0.1-4%	Irregular	50-75µm	50-70Å	140-170m ² /g	N/A	No
	50g, 12pcs	140000097	30mL	300psi / 20bar	32mL/min	50mg-2.0g 0.1-4%	Irregular	50-75µm	50-70Å	140-170m ² /g	N/A	No
	80g, 12pcs	140000098	48mL	300psi / 20bar	40mL/min	80mg-3.2g 0.1-4%	Irregular	50-75µm	50-70Å	140-170m ² /g	N/A	No
	160g, 10pcs	140000099	105mL	250psi/ 17bar	60mL/min	160mg-6.4g 0.1-4%	Irregular	50-75µm	50-70Å	140-170m ² /g	N/A	No
	240g, 10pcs	140000100	148mL	250psi/ 17bar	85mL/min	240mg-9.6g 0.1-4%	Irregular	50-75µm	50-70Å	140-170m ² /g	N/A	No
	440g, 6pcs	140000101	260mL	180psi/ 12bar	120mL/min	440mg-17.6g 0.1-4%	Irregular	50-75µm	50-70Å	140-170m ² /g	N/A	No
	660g, 5pcs	140000102	405mL	180psi/ 12bar	130mL/min	660mg-26.4g 0.1-4%	Irregular	50-75µm	50-70Å	140-170m ² /g	N/A	No
	1600g, 3pcs	140000103	860mL	100psi / 7bar	180mL/min	1.6g-64g 0.1-4%	Irregular	50-75µm	50-70Å	140-170m ² /g	N/A	No
	3200g, 2pcs	140000104	1680mL	100psi / 7bar	200mL/min	3.2g-128g 0.1-4%	Irregular	50-75µm	50-70Å	140-170m ² /g	N/A	No
FlashPure EcoFlex Alumina Basic	8g, 20pcs	140000075	6mL	300psi / 20bar	15mL/min	8mg-0.32g 0.1-4%	Irregular	50-75µm	50-70Å	140-170m ² /g	N/A	No
	24g, 18pcs	140000076	20mL	300psi / 20bar	30mL/min	24mg-1.0g 0.1-4%	Irregular	50-75µm	50-70Å	140-170m ² /g	N/A	No
	50g, 12pcs	140000077	30mL	300psi / 20bar	32mL/min	50mg-2.0g 0.1-4%	Irregular	50-75µm	50-70Å	140-170m ² /g	N/A	No
	80g, 12pcs	140000078	48mL	300psi / 20bar	40mL/min	80mg-3.2g 0.1-4%	Irregular	50-75µm	50-70Å	140-170m ² /g	N/A	No

		BUCHI part number	Column volume	Max. pressure	Default flow rate	Loading capacity	Particle shape	Particle size	Pore size	Surface area	Carbon content	End capping
	160g, 10pcs	140000079	105mL	250psi/ 17bar	60mL/min	160mg-6.4g 0.1-4%	Irregular	50-75µm	50-70Å	140-170m ² /g	N/A	No
	240g, 10pcs	140000080	148mL	250psi/ 17bar	85mL/min	240mg-9.6g 0.1-4%	Irregular	50-75µm	50-70Å	140-170m ² /g	N/A	No
	440g, 6pcs	140000081	260mL	180psi/ 12bar	120mL/min	440mg-17.6g 0.1-4%	Irregular	50-75µm	50-70Å	140-170m ² /g	N/A	No
	660g, 5pcs	140000082	405mL	180psi/ 12bar	130mL/min	660mg-26.4g 0.1-4%	Irregular	50-75µm	50-70Å	140-170m ² /g	N/A	No
	1600g, 3pcs	140000083	860mL	100psi / 7bar	180mL/min	1.6g-64g 0.1-4%	Irregular	50-75µm	50-70Å	140-170m ² /g	N/A	No
	3200g, 2pcs	140000084	1680mL	100psi / 7bar	200mL/min	3.2g-128g 0.1-4%	Irregular	50-75µm	50-70Å	140-170m ² /g	N/A	No
FlashPure EcoFlex Alumina Acidic	8g, 20pcs	140000085	6mL	300psi / 20bar	15mL/min	8mg-0.32g 0.1-4%	Irregular	50-75µm	50-70Å	140-170m ² /g	N/A	No
	24g, 18pcs	140000086	20mL	300psi / 20bar	30mL/min	24mg-1.0g 0.1-4%	Irregular	50-75µm	50-70Å	140-170m ² /g	N/A	No
	50g, 12pcs	140000087	30mL	300psi / 20bar	32mL/min	50mg-2.0g 0.1-4%	Irregular	50-75µm	50-70Å	140-170m ² /g	N/A	No
	80g, 12pcs	140000088	48mL	300psi / 20bar	40mL/min	80mg-3.2g 0.1-4%	Irregular	50-75µm	50-70Å	140-170m ² /g	N/A	No
	160g, 10pcs	140000089	105mL	250psi/ 17bar	60mL/min	160mg-6.4g 0.1-4%	Irregular	50-75µm	50-70Å	140-170m ² /g	N/A	No
	240g, 10pcs	140000090	148mL	250psi/ 17bar	85mL/min	240mg-9.6g 0.1-4%	Irregular	50-75µm	50-70Å	140-170m ² /g	N/A	No
	440g, 6pcs	140000091	260mL	180psi/ 12bar	120mL/min	440mg-17.6g 0.1-4%	Irregular	50-75µm	50-70Å	140-170m ² /g	N/A	No
	660g, 5pcs	140000092	405mL	180psi/ 12bar	130mL/min	660mg-26.4g 0.1-4%	Irregular	50-75µm	50-70Å	140-170m ² /g	N/A	No

		BUCHI part number	Column volume	Max. pressure	Default flow rate	Loading capacity	Particle shape	Particle size	Pore size	Surface area	Carbon content	End capping
	1600g, 3pcs	140000093	860mL	100psi / 7bar	180mL/min	1.6g-64g 0.1-4%	Irregular	50-75µm	50-70Å	140-170m ² /g	N/A	No
	3200g, 2pcs	140000094	1680mL	100psi / 7bar	200mL/min	3.2g-128g 0.1-4%	Irregular	50-75µm	50-70Å	140-170m ² /g	N/A	No
FlashPure EcoFlex Silica LOK	4g, 20pcs	140000032	5.5mL	200psi / 14bar	15mL/min	4mg-0.4g 0.1-10%	Irregular	40-63µm	55-75Å	470-530m ² /g	N/A	No
	12g, 18pcs	140000033	20mL	200psi / 14bar	30mL/min	12mg-1.2g 0.1-10%	Irregular	40-63µm	55-75Å	470-530m ² /g	N/A	No
	24g, 12pcs	140000034	33mL	200psi / 14bar	32mL/min	25mg-2.5g 0.1-10%	Irregular	40-63µm	55-75Å	470-530m ² /g	N/A	No
	40g, 12pcs	140000035	50mL	200psi / 14bar	40mL/min	40mg-4.0g 0.1-10%	Irregular	40-63µm	55-75Å	470-530m ² /g	N/A	No
	80g, 10pcs	140000036	108mL	200psi / 14bar	60mL/min	80mg-8.0g 0.1-10%	Irregular	40-63µm	55-75Å	470-530m ² /g	N/A	No
	120g, 10pcs	140000037	156mL	200psi / 14bar	85mL/min	120mg-12g 0.1-10%	Irregular	40-63µm	55-75Å	470-530m ² /g	N/A	No
	220g, 6pcs	140000038	295mL	150psi / 10bar	120mL/min	220mg-22g 0.1-10%	Irregular	40-63µm	55-75Å	470-530m ² /g	N/A	No
	330g, 5pcs	140000039	405mL	150psi / 10bar	130mL/min	330mg-33g 0.1-10%	Irregular	40-63µm	55-75Å	470-530m ² /g	N/A	No
FlashPure EcoFlex Silica Solid Loader	3.5g, 20pcs	140000040	6mL	200psi / 14bar	15mL/min	3.5mg-0.35g 0.1-10%	Irregular	40-63µm	55-75Å	470-530m ² /g	N/A	No
	10g, 10pcs	140000041	22mL	200psi / 14bar	30mL/min	10mg-1.0g 0.1-10%	Irregular	40-63µm	55-75Å	470-530m ² /g	N/A	No
	20g, 12pcs	140000042	36mL	200psi / 14bar	32mL/min	20mg-2.0g 0.1-10%	Irregular	40-63µm	55-75Å	470-530m ² /g	N/A	No

		BUCHI part number	Column volume	Max. pressure	Default flow rate	Loading capacity	Particle shape	Particle size	Pore size	Surface area	Carbon content	End capping
	35g, 12pcs	140000043	46mL	200psi / 14bar	40mL/min	35mg-3.5g 0.1-10%	Irregular	40-63µm	55-75Å	470-530m ² /g	N/A	No
	70g, 10pcs	140000044	95mL	200psi / 14bar	60mL/min	70mg-7.0g 0.1-10%	Irregular	40-63µm	55-75Å	470-530m ² /g	N/A	No
	100g, 10pcs	140000045	135mL	200psi / 14bar	85mL/min	100mg-10g 0.1-10%	Irregular	40-63µm	55-75Å	470-530m ² /g	N/A	No
	185g, 6pcs	140000046	250mL	150psi / 10bar	120mL/min	185mg-18.5g 0.1-10%	Irregular	40-63µm	55-75Å	470-530m ² /g	N/A	No
	280g, 5pcs	140000047	350mL	150psi / 10bar	130mL/min	280mg-28g 0.1-10%	Irregular	40-63µm	55-75Å	470-530m ² /g	N/A	No
FlashPure EcoFlex C18	4g, 5pcs	140000048	8mL	180psi / 12bar	15mL/min	4mg-0.1g 0.1-2.5%	Spherical	40-60µm	92-108Å	260-360m ² /g	15-17%	Yes
	12g, 5pcs	140000049	24mL	180psi / 12bar	30mL/min	12mg-0.3g 0.1-2.5%	Spherical	40-60µm	92-108Å	260-360m ² /g	15-17%	Yes
	20g, 2pcs	140000050	40mL	180psi / 12bar	32mL/min	20mg-0.5g 0.1-2.5%	Spherical	40-60µm	92-108Å	260-360m ² /g	15-17%	Yes
	40g, 2pcs	140000051	80mL	180psi / 12bar	40mL/min	40mg-1g 0.1-2.5%	Spherical	40-60µm	92-108Å	260-360m ² /g	15-17%	Yes
	80g, 2pcs	140000052	160mL	180psi / 12bar	60mL/min	80mg-2g 0.1-2.5%	Spherical	40-60µm	92-108Å	260-360m ² /g	15-17%	Yes
	120g, 2pcs	140000053	240mL	180psi / 12bar	85mL/min	120mg-3g 0.1-2.5%	Spherical	40-60µm	92-108Å	260-360m ² /g	15-17%	Yes
	220g, 1pc	140000054	400mL	180psi / 12bar	120mL/min	220mg-5.5g 0.1-2.5%	Spherical	40-60µm	92-108Å	260-360m ² /g	15-17%	Yes
	330g, 1pc	140000055	600mL	180psi / 12bar	130mL/min	330mg-8.25g 0.1-2.5%	Spherical	40-60µm	92-108Å	260-360m ² /g	15-17%	Yes

		BUCHI part number	Column volume	Max. pressure	Default flow rate	Loading capacity	Particle shape	Particle size	Pore size	Surface area	Carbon content	End capping
	800g, 1pc	140000056	1700mL	140psi / 9bar	180mL/min	800mg-20g 0.1-2.5%	Spherical	40-60µm	92-108Å	260-360m ² /g	15-17%	Yes
	1500g, 1pc	140000057	2500mL	84psi / 5bar	200mL/min	1500mg-37.5g 0.1-2.5%	Spherical	40-60µm	92-108Å	260-360m ² /g	15-17%	Yes
	3000g, 1pc	140000058	5600mL	84psi / 5bar	200mL/min	3000mg-75g 0.1-2.5%	Spherical	40-60µm	92-108Å	260-360m ² /g	15-17%	Yes
FlashPure EcoFlex Amino	4g, 5pcs	140000059	8mL	180psi / 12bar	15mL/min	4mg-0.2g 0.1-5%	Spherical	40-60µm	92-108Å	260-360m ² /g	4-6%	No
	12g, 5pcs	140000060	24mL	180psi / 12bar	30mL/min	12mg-0.6g 0.1-5%	Spherical	40-60µm	92-108Å	260-360m ² /g	4-6%	No
	20g, 2pcs	140000061	40mL	180psi / 12bar	32mL/min	20mg-1g 0.1-5%	Spherical	40-60µm	92-108Å	260-360m ² /g	4-6%	No
	40g, 2pcs	140000062	80mL	180psi / 12bar	40mL/min	40mg-2g 0.1-5%	Spherical	40-60µm	92-108Å	260-360m ² /g	4-6%	No
	80g, 2pcs	140000063	160mL	180psi / 12bar	60mL/min	80mg-4g 0.1-5%	Spherical	40-60µm	92-108Å	260-360m ² /g	4-6%	No
	120g, 2pcs	140000064	240mL	180psi / 12bar	85mL/min	120mg-6g 0.1-5%	Spherical	40-60µm	92-108Å	260-360m ² /g	4-6%	No
	220g, 1pc	140000065	400mL	180psi / 12bar	120mL/min	220mg-11g 0.1-5%	Spherical	40-60µm	92-108Å	260-360m ² /g	4-6%	No
	330g, 1pc	140000066	600mL	180psi / 12bar	130mL/min	330mg-16.5g 0.1-5%	Spherical	40-60µm	92-108Å	260-360m ² /g	4-6%	No
FlashPure EcoFlex Diol	4g, 5pcs	140000067	8mL	180psi / 12bar	15mL/min	4mg-0.2g 0.1-5%	Spherical	40-60µm	92-108Å	260-360m ² /g	≥4%	No
	12g, 5pcs	140000068	24mL	180psi / 12bar	30mL/min	12mg-0.6g 0.1-5%	Spherical	40-60µm	92-108Å	260-360m ² /g	≥4%	No
	20g, 2pcs	140000069	40mL	180psi / 12bar	32mL/min	20mg-1g 0.1-5%	Spherical	40-60µm	92-108Å	260-360m ² /g	≥4%	No

		BUCHI part number	Column volume	Max. pressure	Default flow rate	Loading capacity	Particle shape	Particle size	Pore size	Surface area	Carbon content	End capping
	40g, 2pcs	140000070	80mL	180psi / 12bar	40mL/min	40mg-2g 0.1-5%	Spherical	40-60µm	92-108Å	260-360m ² /g	≥4%	No
	80g, 2pcs	140000071	160mL	180psi / 12bar	60mL/min	80mg-4g 0.1-5%	Spherical	40-60µm	92-108Å	260-360m ² /g	≥4%	No
	120g, 2pcs	140000072	240mL	180psi / 12bar	85mL/min	120mg-6g 0.1-5%	Spherical	40-60µm	92-108Å	260-360m ² /g	≥4%	No
	220g, 1pc	140000073	400mL	180psi / 12bar	120mL/min	220mg-11g 0.1-5%	Spherical	40-60µm	92-108Å	260-360m ² /g	≥4%	No
	330g, 1pc	140000074	600mL	180psi / 12bar	130mL/min	330mg-16.5g 0.1-5%	Spherical	40-60µm	92-108Å	260-360m ² /g	≥4%	No

FlashPure

FlashPure Silica	4g, 20pcs	11067703	6mL	245psi / 16 bar	15mL/min	4mg-0.8g 0.1-20%	Irregular	35-45µm	53-80Å	500-600m ² /g	N/A	No
	12g, 20pcs	11067704	24mL	245psi / 16 bar	30mL/min	12mg-2.4g 0.1-20%	Irregular	35-45µm	53-80Å	500-600m ² /g	N/A	No
	24g, 15pcs	11067705	35mL	245psi / 16 bar	32 mL/min	24mg-4.8g 0.1-20%	Irregular	35-45µm	53-80Å	500-600m ² /g	N/A	No
	40g, 15pcs	11067706	57mL	245psi / 16 bar	40mL/min	40mg-8g 0.1-20%	Irregular	35-45µm	53-80Å	500-600m ² /g	N/A	No
	80g, 12pcs	11067707	114mL	245psi / 16 bar	60mL/min	80mg-16g 0.1-20%	Irregular	35-45µm	53-80Å	500-600m ² /g	N/A	No
	120g, 10pcs	11067708	159mL	245psi / 16 bar	85mL/min	120mg-24g 0.1-20%	Irregular	35-45µm	53-80Å	500-600m ² /g	N/A	No
	220g, 6pcs	11067709	332mL	165psi / 11bar	120mL/min	220mg-44g 0.1-20%	Irregular	35-45µm	53-80Å	500-600m ² /g	N/A	No
	330g, 4pcs	11067710	472mL	110psi / 7 bar	130mL/min	330mg-66g 0.1-20%	Irregular	35-45µm	53-80Å	500-600m ² /g	N/A	No

		BUCHI part number	Column volume	Max. pressure	Default flow rate	Loading capacity	Particle shape	Particle size	Pore size	Surface area	Carbon content	End capping
FlashPure ID												
FlashPure ID Silica	4g, 20pcs	145146130	5mL	245psi / 16bar	15mL/min	4mg-0.8g 0.1-20%	Irregular	35-45µm	53-80Å	500-600m ² /g	N/A	No
	12g, 20pcs	145146131	24mL	245psi / 16bar	30mL/min	12mg-2.4g 0.1-20%	Irregular	35-45µm	53-80Å	500-600m ² /g	N/A	No
	24g, 15pcs	145165730	35mL	245psi / 16bar	32mL/min	24mg-4.8g 0.1-20%	Irregular	35-45µm	53-80Å	500-600m ² /g	N/A	No
	40g, 15pcs	145146132	57mL	245psi / 16bar	40mL/min	40mg-8g 0.1-20%	Irregular	35-45µm	53-80Å	500-600m ² /g	N/A	No
	80g, 12pcs	145146133	114mL	245psi / 16bar	60mL/min	80mg-16g 0.1-20% c	Irregular	35-45µm	53-80Å	500-600m ² /g	N/A	No
	120g, 10pcs	145146134	159mL	245psi / 16bar	85mL/min	120mg-24g 0.1-20%	Irregular	35-45µm	53-80Å	500-600m ² /g	N/A	No
	220g, 6pcs	145165750	332mL	165psi / 11bar	120mL/min	220mg-44g 0.1-20%	Irregular	35-45µm	53-80Å	500-600m ² /g	N/A	No
	330g, 4pcs	145146135	472mL	110psi / 7bar	130mL/min	330mg-66g 0.1-20%	Irregular	35-45µm	53-80Å	500-600m ² /g	N/A	No
FlashPure ID C18												
	4g, 1pc	145152990	6mL	245psi / 16bar	15mL/min	5mg-0.2g 0.1-5%	Irregular	35-45µm	53-80Å	500-600m ² /g	17-18%	Yes
	12g, 1pc	145152103	24mL	245psi / 16bar	30mL/min	15mg-0.6g 0.1-5%	Irregular	35-45µm	53-80Å	500-600m ² /g	17-18%	Yes
	24g, 1pc	145171532	35mL	245psi / 16bar	32mL/min	38mg-1.2 0.1-5% g	Irregular	35-45µm	53-80Å	500-600m ² /g	17-18%	Yes
	40g, 1pc	145152104	57mL	245psi / 16bar	40mL/min	45mg-2g 0.1-5%	Irregular	35-45µm	53-80Å	500-600m ² /g	17-18%	Yes
	80g, 1pc	145152105	114mL	245psi / 16bar	60mL/min	90mg-4g 0.1-5%	Irregular	35-45µm	53-80Å	500-600m ² /g	17-18%	Yes

		BUCHI part number	Column volume	Max. pressure	Default flow rate	Loading capacity	Particle shape	Particle size	Pore size	Surface area	Carbon content	End capping
	120g, 1pc	145152991	159mL	245psi / 16bar	85mL/min	150mg-6g 0.1-5%	Irregular	35-45µm	53-80Å	500-600m ² /g	17-18%	Yes
	220g, 1pc	145171538	332mL	165psi / 11bar	120mL/min	275mg-11g 0.1-5%	Irregular	35-45µm	53-80Å	500-600m ² /g	17-18%	Yes
	330g, 1pc	145164430	472mL	110psi / 7bar	130mL/min	400mg-16.5g 0.1-5%	Irregular	35-45µm	53-80Å	500-600m ² /g	17-18%	Yes
FlashPure ID Amino	4g, 1pc	145157330	6mL	245psi / 16bar	15mL/min	5mg-0.2g 0.1-5%	Irregular	35-45µm	53-80Å	500-600m ² /g	4-5%	No
	12g, 1pc	145157331	24mL	245psi / 16bar	30mL/min	15mg-0.6g 0.1-5%	Irregular	35-45µm	53-80Å	500-600m ² /g	4-5%	No
	24g, 1pc	140000017	35mL	245psi / 16bar	32mL/min	38mg-1.2g 0.1-5%	Irregular	35-45µm	53-80Å	500-600m ² /g	4-5%	No
	40g, 1pc	145157332	57mL	245psi / 16bar	40mL/min	45mg-2g 0.1-5%	Irregular	35-45µm	53-80Å	500-600m ² /g	4-5%	No
	80g, 1pc	145157333	114mL	245psi / 16bar	60mL/min	90mg-4g 0.1-5%	Irregular	35-45µm	53-80Å	500-600m ² /g	4-5%	No
	120g, 1pc	145157334	159mL	245psi / 16bar	85mL/min	150mg-6g 0.1-5%	Irregular	35-45µm	53-80Å	500-600m ² /g	4-5%	No
	220g, 1pc	140000145	332mL	165psi / 11bar	120mL/min	275mg-11g 0.1-5%	Irregular	35-45µm	53-80Å	500-600m ² /g	4-5%	No
	330g, 1pc	140000146	472mL	110psi / 7bar	130mL/min	400mg-16.5g 0.1-5%	Irregular	35-45µm	53-80Å	500-600m ² /g	4-5%	No
FlashPure ID Amino	4g, 10pcs	145159570	6mL	245psi / 16bar	15mL/min	5mg-0.2g 0.1-5%	Irregular	35-45µm	53-80Å	500-600m ² /g	4-5%	No
	12g, 10pcs	145159571	24mL	245psi / 16bar	30mL/min	15mg-0.6g 0.1-5%	Irregular	35-45µm	53-80Å	500-600m ² /g	4-5%	No

		BUCHI part number	Column volume	Max. pressure	Default flow rate	Loading capacity	Particle shape	Particle size	Pore size	Surface area	Carbon content	End capping
	24g, 10pcs	140000147	35mL	245psi / 16bar	32mL/min	38mg-1.2g 0.1-5%	Irregular	35-45µm	53-80Å	500-600m ² /g	4-5%	No
	40g, 10pcs	145159572	57mL	245psi / 16bar	40mL/min	45mg-2g 0.1-5%	Irregular	35-45µm	53-80Å	500-600m ² /g	4-5%	No
	80g, 10pcs	145162020	114mL	245psi / 16bar	60mL/min	90mg-4g 0.1-5%	Irregular	35-45µm	53-80Å	500-600m ² /g	4-5%	No
	120g, 10pcs	145159573	159mL	245psi / 16bar	85mL/min	150mg-6g	Irregular	35-45µm	53-80Å	500-600m ² /g	4-5%	No
	220g, 10pcs	140000148	332mL	165psi / 11bar	120mL/min	275mg-11g 0.1-5%	Irregular	35-45µm	53-80Å	500-600m ² /g	4-5%	No
	330g, 10pcs	140000149	472mL	110psi / 7bar	130mL/min	400mg-16.5g 0.1-5%	Irregular	35-45µm	53-80Å	500-600m ² /g	4-5%	No
FlashPure ID Diol	4g, 1pc	145157335	6mL	245psi / 16bar	15mL/min	5mg-0.2g 0.1-5%	Irregular	35-45µm	53-80Å	500-600m ² /g	5-7%	No
	12g, 1pc	145157336	24mL	245psi / 16bar	30mL/min	15mg-0.6g 0.1-5%	Irregular	35-45µm	53-80Å	500-600m ² /g	5-7%	No
	24g, 1pc	140000018	35mL	245psi / 16bar	32mL/min	38mg-1.2g 0.1-5%	Irregular	35-45µm	53-80Å	500-600m ² /g	5-7%	No
	40g, 1pc	145157337	57mL	245psi / 16bar	40mL/min	45mg-2g 0.1-5%	Irregular	35-45µm	53-80Å	500-600m ² /g	5-7%	No
	80g, 1pc	145157338	114mL	245psi / 16bar	60mL/min	90mg-4g 0.1-5%	Irregular	35-45µm	53-80Å	500-600m ² /g	5-7%	No
	120g, 1pc	145157339	159mL	245psi / 16bar	85mL/min	150mg-6g 0.1-5%	Irregular	35-45µm	53-80Å	500-600m ² /g	5-7%	No
	220g, 1pc	140000150	332mL	165psi / 11bar	120mL/min	275mg-11g 0.1-5%	Irregular	35-45µm	53-80Å	500-600m ² /g	5-7%	No
	330g, 1pc	140000151	472mL	110psi / 7bar	130mL/min	400mg-16.5g 0.1-5%	Irregular	35-45µm	53-80Å	500-600m ² /g	5-7%	No

		BUCHI part number	Column volume	Max. pressure	Default flow rate	Loading capacity	Particle shape	Particle size	Pore size	Surface area	Carbon content	End capping
FlashPure ID C18-WP	4g, 1pc	145169482	6mL	245psi / 16bar	15mL/min	5mg-0.2g 0.1-5%	Irregular	16-24µm	200-250Å	500-600m ² /g	14.5-17.5%	Yes
	12g, 1pc	145169483	24mL	245psi / 16bar	20mL/min	15mg-0.6g 0.1-5%	Irregular	16-24µm	200-250Å	500-600m ² /g	14.5-17.5%	Yes
	24g, 1pc	140000019	35mL	245psi / 16bar	20mL/min	38mg-1.2g 0.1-5%	Irregular	16-24µm	200-250Å	500-600m ² /g	14.5-17.5%	Yes
	40g, 1pc	145169484	57mL	245psi / 16bar	30mL/min	45mg-2g 0.1-5%	Irregular	16-24µm	200-250Å	500-600m ² /g	14.5-17.5%	Yes
	80g, 1pc	140000152	114mL	245psi / 16bar	40mL/min	90mg-4g 0.1-5%	Irregular	16-24µm	200-250Å	500-600m ² /g	14.5-17.5%	Yes
	120g, 1pc	140000153	159mL	245psi / 16bar	45mL/min	150mg-6g 0.1-5%	Irregular	16-24µm	200-250Å	500-600m ² /g	14.5-17.5%	Yes
	220g, 1pc	140000154	332mL	165psi / 11bar	65mL/min	275mg-11g 0.1-5%	Irregular	16-24µm	200-250Å	500-600m ² /g	14.5-17.5%	Yes
	330g, 1pc	140000155	472mL	110psi / 7bar	65mL/min	400mg-16.5g 0.1-5%	Irregular	16-24µm	200-250Å	500-600m ² /g	14.5-17.5%	Yes
FlashPure ID HP												
FlashPure ID HP Silica	4g, 20pcs	145170200	6mL	245psi / 16bar	15mL/min	4mg-0.8g 0.1-20%	Irregular	16-24µm	60-75Å	500-600m ² /g	N/A	No
	12g, 20pcs	145170201	24mL	245psi / 16bar	30mL/min	12mg-2.4g 0.1-20%	Irregular	16-24µm	60-75Å	500-600m ² /g	N/A	No
	24g, 15pcs	145170202	35mL	245psi / 16bar	32mL/min	24mg-4.8g 0.1-20%	Irregular	16-24µm	60-75Å	500-600m ² /g	N/A	No
	40g, 15pcs	145170203	57mL	245psi / 16bar	40mL/min	40mg-8g 0.1-20%	Irregular	16-24µm	60-75Å	500-600m ² /g	N/A	No
	80g, 12pcs	145170204	114mL	245psi / 16bar	60mL/min	80mg-16g 0.1-20%	Irregular	16-24µm	60-75Å	500-600m ² /g	N/A	No
	120g, 10pcs	145170205	159mL	245psi / 16bar	80mL/min	120mg-24g 0.1-20%	Irregular	16-24µm	60-75Å	500-600m ² /g	N/A	No

		BUCHI part number	Column volume	Max. pressure	Default flow rate	Loading capacity	Particle shape	Particle size	Pore size	Surface area	Carbon content	End capping
	220g, 6pcs	145170207	332mL	165psi / 11bar	120mL/min	220mg-44g 0.1-20%	Irregular	16-24µm	60-75Å	500-600m ² /g	N/A	No
	330g, 4pcs	145170208	472mL	110psi / 7bar	130mL/min	330mg-66g 0.1-20%	Irregular	16-24µm	60-75Å	500-600m ² /g	N/A	No
FlashPure Select												
FlashPure Select Silica	4g, 20pcs	140000113	8mL	400psi / 27bar	12mL/min	4mg-1.2g 0.1-30%	Spherical	13-17µm	30-70Å	600-800m ² /g	N/A	No
	12g, 18pcs	140000114	24mL	400psi / 27bar	24mL/min	12mg-3.6g 0.1-30%	Spherical	13-17µm	30-70Å	600-800m ² /g	N/A	No
	25g, 12pcs	140000115	39mL	400psi / 27bar	25mL/min	25mg-7.5g 0.1-30%	Spherical	13-17µm	30-70Å	600-800m ² /g	N/A	No
	40g, 12pcs	140000116	52mL	400psi / 27bar	32mL/min	40mg-12g 0.1-30%	Spherical	13-17µm	30-70Å	600-800m ² /g	N/A	No
	80g, 10pcs	140000117	120mL	350psi / 24bar	48mL/min	80mg-24g 0.1-30%	Spherical	13-17µm	30-70Å	600-800m ² /g	N/A	No
	120g, 10pcs	140000118	180mL	300psi / 20bar	68mL/min	120mg-36g 0.1-30%	Spherical	13-17µm	30-70Å	600-800m ² /g	N/A	No
	220g, 6pcs	140000119	320mL	300psi / 20bar	96mL/min	220mg-66g 0.1-30%	Spherical	13-17µm	30-70Å	600-800m ² /g	N/A	No
	330g, 5pcs	140000120	450mL	250psi / 17bar	104mL/min	330mg-99g 0.1-30%	Spherical	13-17µm	30-70Å	600-800m ² /g	N/A	No
FlashPure Select C18	4g, 5pcs	140000121	8mL	180psi / 12bar	15mL/min	4mg-0.2g 0.1-5%	Spherical	20-35µm	92-108Å	300-340m ² /g	17-19%	Yes
	12g, 5pcs	140000122	24mL	180psi / 12bar	30mL/min	12mg-0.6g 0.1-5%	Spherical	20-35µm	92-108Å	300-340m ² /g	17-19%	Yes

		BUCHI part number	Column volume	Max. pressure	Default flow rate	Loading capacity	Particle shape	Particle size	Pore size	Surface area	Carbon content	End capping
	20g, 2pcs	140000123	40mL	180psi / 12bar	32mL/min	20mg-1g 0.1-5%	Spherical	20-35µm	92-108Å	300-340m ² /g	17-19%	Yes
	40g, 2pcs	140000124	80mL	180psi / 12bar	40mL/min	40mg-2g 0.1-5%	Spherical	20-35µm	92-108Å	300-340m ² /g	17-19%	Yes
	80g, 2pcs	140000125	160mL	180psi / 12bar	60mL/min	80mg-4g 0.1-5%	Spherical	20-35µm	92-108Å	300-340m ² /g	17-19%	Yes
	120g, 2pcs	140000126	240mL	180psi / 12bar	85mL/min	120mg-6g 0.1-5%	Spherical	20-35µm	92-108Å	300-340m ² /g	17-19%	Yes
	220g, 1pc	140000127	400mL	180psi / 12bar	120mL/min	220mg-11g 0.1-5%	Spherical	20-35µm	92-108Å	300-340m ² /g	17-19%	Yes
	330g, 1pc	140000128	600mL	180psi / 12bar	130mL/min	330mg-16.5g 0.1-5%	Spherical	20-35µm	92-108Å	300-340m ² /g	17-19%	Yes
FlashPure Select Amino	4g, 5pcs	140000129	8mL	180psi / 12bar	15mL/min	4mg-0.4g 0.1-10%	Spherical	20-35µm	92-108Å	300-340m ² /g	4-6%	No
	12g, 5pcs	140000130	24mL	180psi / 12bar	30mL/min	12mg-1.2g 0.1-10%	Spherical	20-35µm	92-108Å	300-340m ² /g	4-6%	No
	20g, 2pcs	140000131	40mL	180psi / 12bar	32mL/min	20mg-2g 0.1-5%	Spherical	20-35µm	92-108Å	300-340m ² /g	4-6%	No
	40g, 2pcs	140000132	80mL	180psi / 12bar	40mL/min	40mg-4g 0.1-10%	Spherical	20-35µm	92-108Å	300-340m ² /g	4-6%	No
	80g, 2pcs	140000133	160mL	180psi / 12bar	60mL/min	80mg-8g 0.1-10%	Spherical	20-35µm	92-108Å	300-340m ² /g	4-6%	No
	120g, 2pcs	140000134	240mL	180psi / 12bar	85mL/min	120mg-12g 0.1-10%	Spherical	20-35µm	92-108Å	300-340m ² /g	4-6%	No
	220g, 1pc	140000135	400mL	180psi / 12bar	120mL/min	220mg-22g 0.1-10%	Spherical	20-35µm	92-108Å	300-340m ² /g	4-6%	No
	330g, 1pc	140000136	600mL	180psi / 12bar	130mL/min	330mg-33g 0.1-10%	Spherical	20-35µm	92-108Å	300-340m ² /g	4-6%	No

		BUCHI part number	Column volume	Max. pressure	Default flow rate	Loading capacity	Particle shape	Particle size	Pore size	Surface area	Carbon content	End capping
FlashPure Select Diol	4g, 5pcs	140000137	8mL	180psi / 12bar	15mL/min	4mg-0.4g 0.1-10%	Spherical	20-35µm	92-108Å	300-340m ² /g	4-6%	No
	12g, 5pcs	140000138	24mL	180psi / 12bar	30mL/min	12mg-1.2g 0.1-10%	Spherical	20-35µm	92-108Å	300-340m ² /g	4-6%	No
	20g, 2pcs	140000139	40mL	180psi / 12bar	32mL/min	20mg-2g 0.1-10%	Spherical	20-35µm	92-108Å	300-340m ² /g	4-6%	No
	40g, 2pcs	140000140	80mL	180psi / 12bar	40mL/min	40mg-4g 0.1-10%	Spherical	20-35µm	92-108Å	300-340m ² /g	4-6%	No
	80g, 2pcs	140000141	16mL	180psi / 12bar	60mL/min	80mg-8g 0.1-10%	Spherical	20-35µm	92-108Å	300-340m ² /g	4-6%	No
	120g, 2pcs	140000142	240mL	180psi / 12bar	80mL/min	120mg-12g 0.1-10%	Spherical	20-35µm	92-108Å	300-340m ² /g	4-6%	No
	220g, 1pcs	140000143	400mL	180psi / 12bar	120mL/min	220mg-22g 0.1-10%	Spherical	20-35µm	92-108Å	300-340m ² /g	4-6%	No
	330g, 1 pcs	140000144	600mL	180psi / 12bar	130mL/min	330mg-33g 0.1-10%	Spherical	20-35µm	92-108Å	300-340m ² /g	4-6%	No

000 «Диаэм»

Москва

ул. Магаданская, д. 7, к. 3 ■ тел./факс: (495) 745-0508 ■ sales@dia-m.ru

www.dia-m.ru

С.-Петербург

+7 (812) 372-6040
spb@dia-m.ru

Казань

+7(843) 210-2080
kazan@dia-m.ru

Новосибирск

+7(383) 328-0048
nsk@dia-m.ru

Ростов-на-Дону

+7 (863) 303-5500
rnd@dia-m.ru

Воронеж

+7 (473) 232-4412
vrn@dia-m.ru

Екатеринбург

+7 (912) 658-7606
ekb@dia-m.ru

Йошкар-Ола

+7 (927) 880-3676
nba@dia-m.ru

Кемерово

+7 (923) 158-6753
kemerovo@dia-m.ru

Красноярск

+7(923) 303-0152
krsk@dia-m.ru

Армения

+7 (094) 01-0173
armenia@dia-m.ru

